

MANICALAND STATE UNIVERSITY OF APPLIED SCIENCES

FACULTY OF ENGINEERING

DEPARTMENT OF CHEMICAL AND PROCESSING ENGINEERING

FLUID FLOW, THERMOFLUIDS

CODE: HCHE 223/HMIE 225

SESSIONAL EXAMINATIONS

APRIL 2021

DURATION: 3 HOURS

EXAMINER: MR C.K. SIMENDE

INSTRUCTIONS

1. Answer **any 4** questions.
 2. Each question carries 25 marks.
 3. Total marks 100
-

QUESTION 1

- a. Define the following terms as they are used in fluid flow and thermofluids:
- i) Fluid statics [1 mark]
 - ii) Fluid mechanics [2 marks]
 - iii) Reynolds number [2 marks]
- b. Calculate the Reynolds number if a liquid of viscosity 0.5 Ns/m^2 and relative density of 500 kg/m^3 through a 10 mm pipe flows with a velocity of 3 m/s. [4 marks]
- c. A dam holds back the water in a lake. If the dam has a small hole 1.4 meters below the surface of the lake, at what speed does water exit the hole? [10 marks]
- d. Outline the main industrial applications of Fluid mechanics [6 marks]

QUESTION 2

- a. If a 25 litre volume of oil has a mass of 20 kilograms, determine the oil's:
- i) Mass density [2 marks]
 - ii) Weight density [2 marks]
 - iii) Relative density [2 marks]
 - iv) Specific volume [2 marks]
- b. Determine whether the flow is laminar or turbulent given that a fluid having a viscosity of 0.4 Ns/m^2 and relative density of 900 kg/m^3 flows through a pipe of 20mm diameter with a velocity of 2.5m/s. [7 marks]
- c. Define the following types of flow with the aid of equation where possible:
- i) Steady flow [2 marks]
 - ii) Unsteady flow [2 marks]

- iii) Compressible flow [1 mark]
- iv) Incompressible flow [1 mark]
- v) Laminar flow [2 marks]
- vi) Turbulent flow [2 marks]

QUESTION 3

- a. With the aid of a clearly labeled diagram derive the Continuity Equation. [16 marks]
- b. The area of a pipe at section XX^1 is 315cm^2 . The area of pipe at section YY^1 is twice the area of section XX^1 . The velocity at section XX^1 is 4.5m/s . Find the velocity at section YY^1 . Also determine the flow rate through the pipe. [9 marks]

QUESTION 4

- a. State and explain Bernoulli's Theorem [2 marks]
- b. Outline the main assumptions used when deriving the Bernoulli's equation [4 marks]
- c. With the aid of a clearly labeled diagram derive the Bernoulli's equation [9 marks]
- d. Water is flowing through an inclined pipeline of diameter 20cm and 40cm at section A and B respectively. Section A and B are located at height of 2m and 2.5m respectively from ground level. The discharge through the pipe is 30l/s . If the pressure at A is 20kPa , find the pressure at point B. [10 marks]

QUESTION 5

- a. Steam enters a converging-diverging nozzle operating at steady state with $P_1 = 0.05$ MPa, $T_1 = 400^\circ$ C and a velocity of 10 m/s. The steam flows through the nozzle with negligible heat transfer and no significant change in potential energy. At the exit, $P_2 = 0.01$ MPa and the velocity is 665 m/s. The mass flow rate is 2 kg/s. Determine the exit area of the nozzle, in m^2 . [9 marks]

Given data:

$$h_1 = 3278.9 \text{ kJ/kg}$$

$$T_2 = 300^\circ \text{ C}$$

$$v_2 = 26.445 \text{ m}^3/\text{kg}$$

- b. Steam enters a turbine at steady state with a mass flow rate of 4600 kg/h. The turbine develops a power output of 1000Kw. At the inlet the pressure is 0.05 MPa, the temperature is 400° C, and the velocity is 10 m/s. At the exit, the pressure is 10 kPa, the quality is 0.9 and the velocity is 50 m/s. Calculate the rate of heat transfer between the turbine and the surroundings in Kw. [10 marks]

Given data:

$$h_1 = 3278.9 \text{ kJ/kg}$$

$$h_f = 191.83 \text{ kJ/kg}$$

$$h_{fg} = 2392.8 \text{ kJ/kg}$$

- c. Define the following terms as used in the study of thermofluids:

- | | |
|-------------------|-----------|
| i) Control volume | [1 mark] |
| ii) Work flow | [2 marks] |
| iii) Enthalpy | [1 mark] |
| iv) Nozzle | [1 mark] |
| v) Diffuser | [1 mark] |

END OF PAPER